

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (withdrawn) A method of processing data associated with a plurality of data channels comprising:

designating one of the plurality of data channels as a primary channel and designating the other of the plurality of data channels as non-primary channels;

filtering to remove noise from the image data associated with the primary channel less than the image data associated with the non-primary channels;

operating upon said filtered image data in order to obtain resultant data for the primary channel; and

repeating each of the designating, filtering and operating steps for each of the other plurality of channels, such that each channel is designated a primary channel and resultant data is obtained for each of the plurality of channels.

2. (withdrawn) A method according to claim 1, further comprising the step of inputting data obtained from scanning a negative being developed by electronic film development.

3. (withdrawn) A method according to claim 1, further including the step of inputting image data obtained from scanning an image.

4. (withdrawn) A method according to claim 1 wherein the step of filtering does not filter to remove noise from the image data associated with the primary channel.

5. (withdrawn) A method according to claim 1 wherein the image data is operated upon one pixel at a time.

6. (withdrawn) A method according to claim 1 wherein a group of pixels are used to determine the resultant data for each pixel.

7. (withdrawn) A method of processing image data associated with red, green and blue color channels obtained from an image comprising the steps of:

designating one of the red, green and blue color channels as a first primary channel and designating the other channels as non-primary channels, such that image data associated with the first primary channel can be operated upon independently of the image data associated with the non-primary channels;

filtering to remove noise from the image data associated with first primary channel less than the image data associated with the non-primary channels to obtain first filtered image data;

operating upon said first filtered image data in order to obtain first resultant data for the first primary channel;

designating one of the non-selected red, green and blue color channels as the second primary channel and designating the other channels as non-primary channels, such that image data associated with the second primary channel can be operated upon independently of the image data associated with the non-primary channels;

filtering to remove noise from the image data associated with second primary channel less than the image data associated with the non-primary channels to obtain second filtered image data;

operating upon said second filtered image data in order to obtain second resultant data for the second primary channel;

designating the remaining non-selected red, green and blue color channels as the third primary channel and designating the other channels as non-primary channels, such that image data associated with the third primary channel can be operated upon independently of the image data associated with the non-primary channels;

filtering to remove noise the image data associated with third primary channel less than the image data associated with the non-primary channels to obtain third filtered image data; and

operating upon said third filtered image data in order to obtain third resultant data for the third primary channel.

8. (withdrawn) A method according to claim 7, further including the step of inputting image data obtained from scanning a negative being developed by electronic film development.

9. (withdrawn) A method according to claim 7, further including the step of inputting image data obtained from scanning an image.

10. (withdrawn) A method according to claim 7 wherein each of the steps of filtering does not filter the image data associated with the primary channel.

11. (withdrawn) An apparatus for processing image data associated with a plurality of channels obtained from an image comprising:
a computer processor; and
an application program executed by the processor, the application program implementing a:

method for designating one of the plurality of channels as a primary channel and designating the other of the plurality of channels as non-primary channels, such that image data associated with the primary channel can be operated upon independently of the image data associated with the non-primary channels;

method for noise filtering the image data associated with primary channel less than the image data associated with the non-primary channels; and

method for operating upon said filtered image data in order to obtain resultant data for the primary channel.

12. (withdrawn) An apparatus according to claim 12, further including means for inputting image data obtained from scanning a negative being developed by electronic film development.

13. (withdrawn) An apparatus according to claim 12, further including means for inputting image data obtained from scanning a positive image.

14. (withdrawn) An apparatus according to claim 12, wherein the means for filtering does not filter the image data associated with the primary channel.

15. (presently amended) A method for correcting image information associated with a plurality of information channels comprising:

obtaining image information from a first information channel which is a primary information channel to be reconstructed;

obtaining image information from at least one additional information channel, wherein at least a portion of the information from the at least one additional information channel includes information associated with the information obtained from the first channel;

transforming only the image information obtained from the at least one additional information channel to obtain transformed image information associated with the first channel; and

combining at least a portion of the transformed image information associated with the first information channel with at least a portion of the information from the first information channel to obtain corrected image information associated with the first information channel, wherein said corrected image information defines a reconstructed information channel that corresponds to said primary information channel.

16. (original) The method as in Claim 15, wherein transforming comprises filtering the image information obtained from the at least one additional information channel to minimize noise.

17. (original) The method as in Claim 15, wherein the method implements a color correction matrix.

18. (original) The method as in Claim 15, wherein the image information to be corrected is from a photographic image.

19. (original) The method as in Claim 15, further comprising obtaining image information from a third information channel, wherein the first information channel is a first color channel, the at least one additional information channel is a second color channel, and the third information channel is a third color channel.

20. (original) The method as in Claim 15, wherein at least a portion of the information obtained from the first channel includes information associated with the information obtained from the at least one additional channel, and wherein the method further comprises:

transforming the image information obtained from the first information channel to obtain transformed image information associated with the at least one additional channel; and

combining at least a portion of the transformed image information associated with the at least one additional channel with at least a portion of the image information obtained from the at least one additional channel to obtain corrected image information associated with the at least one additional channel.

21. (original) The method as in Claim 20, wherein the image information obtained from the at least one additional image information channel is substantially unaltered before combining.

22. (original) The method as in Claim 15, wherein the information obtained from the first information channel is substantially unaltered before combining.

23. (original) The method as in Claim 15, wherein obtaining image information comprises scanning an image.

24. (original) The method as in Claim 15, wherein obtaining image information comprises scanning a photographic image during development.

25. (presently amended) A digital file tangibly embodied in a computer readable medium, said digital file generated by implementing a method comprising:

obtaining image information from a first information channel
which is a primary information channel to be reconstructed;

obtaining image information from at least one additional information channel, wherein at least a portion of the information from the at least one additional information channel includes information associated with the information obtained from the first channel;

transforming only the image information obtained from the at least one additional information channel to obtain transformed image information associated with the first channel; and

combining at least a portion of the transformed image information associated with the first information channel with at least a portion of the information from the first information channel to obtain corrected image information associated with the first information channel, wherein said corrected image information defines a reconstructed information channel that corresponds to said primary information channel.

26. (original) The digital file as in Claim 25, wherein transforming comprises filtering the image information obtained from the at least one additional information channel to minimize noise.

27. (original) The digital file as in Claim 25, wherein the method implements a color correction matrix.

28. (original) The digital file as in Claim 25, wherein the image information to be corrected is from a photographic image.

29. (original) The digital file as in Claim 25, further comprising obtaining image information from a third information channel, wherein the first information channel is a first color channel, the at least one

additional information channel is a second color channel, and the third information channel is a third color channel.

30. (original) The digital file as in Claim 25, wherein at least a portion of the information obtained from the first channel includes information associated with the information obtained from the at least one additional channel, and wherein the method further comprises:

transforming the image information obtained from the first information channel to obtain transformed image information associated with the at least one additional channel; and

combining at least a portion of the transformed image information associated with the at least one additional channel with at least a portion of the image information obtained from the at least one additional channel to obtain corrected image information associated with the at least one additional channel.

31. (original) The digital file as in Claim 30, wherein the image information obtained from the at least one additional image information channel is substantially unaltered before combining.

32. (original) The digital file as in Claim 25, wherein the image information obtained from the first information channel is substantially unaltered before combining.

33. (original) The digital file as in Claim 25, wherein obtaining image information comprises scanning an image.

34. (original) The digital file as in Claim 25, wherein obtaining image information comprises scanning a photographic image during development.

35. (presently amended) An image processing system comprising:
at least one illumination source capable of illuminating a physical medium;

at least one detector enabled to generate electrical signals in response to light, said electrical signals representative of image information obtained from a first information channel and at least one additional information channel, wherein said first information channel is a primary information channel to be reconstructed, at least a portion of the information from the at least one additional information channel includes information associated with the information obtained from the first channel, and said detector further enabled to output said electrical signals for image processing;

at least one processor;

memory operably associated with said processor; and

a program of instructions, said program of instructions capable of being stored in said memory and executed by said processor, said program of instructions enabled to transform only the image information obtained from the at least one additional information channel to obtain transformed image information associated with the first channel, and to combine at least a portion of the transformed image information associated with the first information channel with at least a portion of the information from the first information channel to obtain corrected image information associated with the first information channel, wherein said corrected image information defines a reconstructed information channel that corresponds to said primary information channel.

36. (original) The image processing system as in Claim 35, wherein said program of instructions is further enabled to filter the image information obtained from the at least one additional information channel to minimize noise.

37. (original) The image processing system as in Claim 35, wherein said program of instructions is enabled to implement a color correction matrix.

38. (original) The image processing system as in Claim 35, wherein the image information to be corrected is from a photographic image.

39. (original) The image processing system as in Claim 35, wherein said electrical signals further represent information from a third information channel, and wherein the first information channel is a first color channel, the at least an additional information channel is a second color channel, and the third information channel is a third color channel.

40. (original) The image processing system as in Claim 35, wherein at least a portion of the information obtained from the first channel includes information associated with the information obtained from the at least one additional channel, and wherein said program of instructions is further enabled to transform the image information obtained from the first information channel to obtain transformed image information associated with the at least one additional channel, and to combine at least a portion of the transformed image information associated with the at least one additional channel with at least a portion of the image information obtained from the at least one additional channel to obtain corrected image information associated with the at least one additional channel.

41. (original) The image processing system as in Claim 40, wherein the image information obtained from the at least one additional image information channel is substantially unaltered before combining.

42. (original) The image processing system as in Claim 35, wherein the image information obtained from the first information channel is substantially unaltered before being combined.

43. (original) The image processing system as in Claim 35, wherein the image processing system is a digital film processing system.

44. (original) The image processing system as in Claim 35, wherein the image processing system is a copy machine.

45. (original) The image processing system as in Claim 35, wherein the image processing system is a facsimile machine.

46. (original) The image processing system as in Claim 35,
wherein the image processing system is a scanner.